

# SPEAKMAN. COM

## LAWS, CODES AND...



OSHA 29 CFR 1910.151, Subpart k, Section c

Where the eyes or body of any person may be exposed to injurious corrosive materials, suitable facilities for quick, drenching or flushing of the eyes and body shall be provided within the work area for immediate emergency use.



416.0 Emergency Eyewash and Shower Equipment

416.1 Application. Emergency eyewash and shower equipment shall comply with ISFA 7358.1.

416.2 Water Supply. Emergency eyewash and shower equipment shall not be limited in the water supply flow rates. Flow rate, discharge pattern, and temperature of flushing fluids shall be provided in accordance with ISEA Z358.1 based on the hazardous material.



411.1 Approval. Emergency showers and eyewash stations shall confirm to ISEA Z358.1.

\$

Thousands of people are blinded each year from work-related eye injuries that could have been prevented with the proper selection and use of eye and face protection. Eye injuries alone cost more than \$300 million per year in lost production time, medical expenses, and worker compensation.

(Retrieved from https://www.osha.gov/SLTC/eyefaceprotection)

## STANDARDS

#### ANSI/ISEA

Z358.1

American National Standard for Emergency Eyewash and Shower Equipment

National consensus standard ANSI/ISEA Z358.1 provides performance, safety, placement and testing details on emergency eyewash and shower equipment.

\* Emergency eyewash and shower equipment should be available for immediate emergency use, but in no instance should it take longer than 10 seconds to reach the nearest facility.

It is recognized that the average person covers a distance of approximately 55 ft. in 10 seconds when walking at a normal pace. Equipment shall be in an accessible location and identified w/ highly visible signs.

\* Delivered flushing fluid temperature shall be tepid, (Typical Range 60°F - 100°F).

Water that is too cold will inhibit someone from using the shower/eyewash for the full 15 minutes. Water that is too hot will cause additional damage to the eyes.

\* Plumbed Emergency Showers & Eyewashes shall be activated weekly for a period long enough to verify operation and ensure that flushing fluid is available, and inspected annually for conformance to the standard.



Each day about 2000 U.S. workers have a job-related eye injury that requires medical treatment. About one third of the injuries are treated in hospital emergency departments and more than 100 of these injuries result in one or more days of lost work.

(Retrieved from http://www.cdc.gov/niosh/topics/eye/)

## 10 SECONDS TO SAFETY



ANSI/ISEA Z358.1 requires that companies provide emergency showers and/or eyewashes within 10 seconds' travel time of a hazard. Look for signage indicating hazardous materials and make sure eyewashes and showers are within the prescribed distance.

## LOOK FOR THESE LABELS

In 2003, the United Nations adopted the Globally Harmonized System (GHS) of Classification and Labeling of Chemicals. The GHS includes criteria for the classification of health, physical and environmental hazards, as well as specifying what information should be included on labels of hazardous chemicals as well as safety data sheets. These are signs of hazardous materials that indicate the need for Emergency Showers and Eyewashes.







|            | Description                               | Bowl Material   | MFG#    |
|------------|---|-----------------|---------|
| <u>ę</u> . | Wall mount eye & face wash                | Plastic         | SE-1000 |
| <u>ę</u> . | Wall mount eye & face wash                | Stainless Steel | SE-1050 |
| <u></u>    | Pedestal mount eye & face wash            | Plastic         | SE-1100 |
| <u>ę</u> . | Pedestal mount eye & face wash            | Stainless Steel | SE-1150 |
| <u>ę</u> . | Combination shower eye & face wash system | Plastic         | SE-1200 |
| <u>ę</u> . | Combination shower eye & face wash system | Stainless Steel | SE-1250 |
|            | Smokey gray cover for the optimus bowl    | n/a             | OCV     |
|            |   |                 |         |



#### TRADITIONAL SERIES COMBINATION SHOWER & EYE/FACE WASH

| Description                              | Frame Material  | Bowl Material   | MFG#          |
|--|-----------------|-----------------|---------------|
| Eye or eye/face wash combination station | Galvanized      | Plastic         | SE-697/SE-695 |
| Eye or eye/face wash combination station | Galvanized      | Stainless Steel | SE-693/SE-690 |
| Eye or eye/face wash combination station | Stainless Steel | Stainless Steel | SE-626/SE-625 |
| Heat-traced combination station          | Galvanized      | n/a             | SE-7000       |



SE-697

SE-625

SE-7000

#### COMBINATION EYEWASH & DRENCH HOSES

| Description  | MFG#       |
|--|------------|
| Wall mounted drench hose with self-closing valve                         | SE-920*    |
| Wall mounted combination Eyewash and drench hose with 12' recoiling hose | SE-925-TEW |
| Counter mounted combination Eyewash and drench hose                      | SE-927     |



SE-925-TEW



SE-927

#### THERMOSTATIC MIXING VALVES

| Description  | MFG#     |
|--|----------|
| Single element valve with 67 gpm capacity of tepid water | SE-350*† |
| Single element valve with 36 gpm capacity of tepid water | SE-362*† |
| Single element valve with 7 gpm capacity of tepid water  | SE-370*† |





SE-362

SE-370



## EYESAVER® COMBINATION EYEWASH & LABORATORY FAUCET

| Description   | MFG#        |
|---|-------------|
| Widespread combination eyewash & faucet                     | SEF-1800-CA |
| Single post combination eyewash & faucet                    | SEF-1850    |
| Combination eyewash and service sink faucet                 | SEF-9000    |
| Eyewash attachment to existing Speakman service sink faucet | SEF-9200    |
| Tepid water kit for SEF-1800-CA, SEF-1850 & SEF-9000        | SEF-TW*     |





SEF-9000

SEF-1850 SEF-1800-CA



### EYE & EYE/FACE WASH

| Description                                  | Bowl Material   | MFG#          |
|--|-----------------|---------------|
| Wall mount eye or eye/ face wash             | Plastic         | SE-580/SE-495 |
| Wall mount eye or eye/face wash              | Stainless Steel | SE-582/SE-490 |
| Pedestal round bowl eye or eye/<br>face wash | Stainless Steel | SE-584/SE-491 |
| Pedestal round bowl eye or eye/<br>face wash | Plastic         | SE-583/SE-496 |







EYE & EYE/FACE WASH

| Description  | MFG#    |
|--|---------|
| Portable pressurized eyewash - 10 gallon capacity  | SE-590  |
| 20 Gallon portable eyewash with pull strap activation complete with SE-4920 drench hose attachment | SE-4300 |
| 9 Gallon GravityFlo® gravity-fed eyewash   | SE-4400 |



SE-4300

SE-4400







SE-575-DP-237

## LABORATORY EYEWASHES & EMERGENCY SHOWERS

| Description  | MFG#          |
|--|---------------|
| Wall mounted emergency shower with recessed shower head                | SE-237        |
| Counter top mounted, swing activated eyewash                           | SE-570        |
| Counter top mounted, paddle handle activated eyewash                   | SE-572        |
| Back deck mounted, pull down activated eyewash                         | SE-573        |
| Swing down eyewash, wall mount with drain pan                          | SE-575-DP     |
| Swing down eyewash, wall mount with drain pan and recessed shower head | SE-575-DP-237 |

## **COMMON HAZARDS**



#### Hazardous Material Storage

The storage, transfer and use of flammable liquids require showers and/or eyewashes as secondary protection. Look for containers used to handle or store these materials and make sure ANSI/ISEA Z358.1 compliant emergency equipment is within 10 seconds' travel distance.



Chemical Storage Cabinets



Cleaning Chemical Storage (Janitor's Closets)



Bulk Chemical Storage



#### Personal Protective Equipment

Look for areas where workers are using personal protective equipment such as goggles and liquid-proof gloves. These are found in areas where hazardous materials are being used and eyewashes and/or showers will be required as secondary protection.



Industrial and Manufacturing Facilities



Chemistry Labs



Paint Booths



#### Battery Charging & Maintenance

OSHA Directive #STD 1-8.2 "provides guidelines regarding eyewash and body flushing facilities required for immediate emergency use in electric storage battery charging and maintenance areas." Make sure emergency equipment is properly located near these hazards.



Fork Lift and Maintenance



Industrial Battery Charging



Automotive Service Shops

## ARE YOU IN COMPLIANCE WITH ANSI/ISEA Z358.1?

|  |  |  |                                 |   | _  |
|--|--|--|---------------------------------|---|--|
| AREA & RECOMMENDATION  | 10 <sup>z</sup> sec.   | 60° 100°                                   |                                 |   |  |
| AREA<br>REC.   | YES / NO   | YES / NO                                   | YES / NO                        | YES / NO  | YES / N O  |
| AREA<br>REC.   | YES / NO   | YES / NO                                   | YES / NO                        | YES / NO  | YES/N O  |
| AREA<br>REC.   | YES / NO   | YES / NO                                   | YES / NO                        | YES / NO  | YES/N O  |
| AREA<br>REC.   | YES / NO   | YES / NO                                   | YES / NO                        | YES / NO  | YES/N O  |
| AREA   | YES / NO   | YES / NO                                   | YES / NO                        | YES / NO  | YES/N O  |
| REC.  AREA  REC.   | YES / NO   | YES / NO                                   | YES / NO                        | YES / NO  | YES / N O  |
| SPEAKMAN®  400 Anchor Mill Rd, New Castle, DE 19720 www.Speakman.com Toll-Free: (800) 537-2107 | Are emergency showers and eyewashes located within 10 seconds travel time of hazard? | ls the flushing fluid Tepid? (60° - 100°F) | Is the equipment tested weekly? | Does the unit function properly and provide hands-free operation? | Is the unit identified with a highly visible sign? |